

INDUSTRIAL COMPONENT DATA

G-EDSWU-M63-L66L-STES-S 1411103 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-EDSWU-M63-L66L-STES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-EDSWU-M63-L66L-STES-S
Catalog number	1411103
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-1874DBB293
Generated	2026-08-06

Product Overview

Cable gland

Cable gland, screwed connection material: 316L stainless steel, application: Ex, cable outer diameter 54.6 mm ... 65.9 mm, shielding: yes, connection thread: M63 x 1.5, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1411103

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 557 (C-3-2017)

GTIN 4046356922180

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 73269098

Country of origin GB (United Kingdom)

Dimensions

Length 107 mm

Thread pitch 1.5 mm

Wrench size, union nut 80 mm

Wrench size, support 80 mm
Hexagon angular dimension 88 mm
Length of the connecting thread 15 mm
External cable diameter 54.6 mm ... 65.9 mm
Cable diameter without cable sheath 47.2 mm ... 56 mm
Armor connection method Cone
Armor thickness 2 mm ... 2.5 mm (Stepped cone side (SWA/...))
0 mm ... 1.5 mm (Grooved cone side (STA/...))
Cable diameter without armor 47.2 mm ... 56 mm (Filler beneath the armor)
Cable types that can be used Depending on the material of the housing wall (SWA/AWA/PWA/STA/ASA/CY/SY/SWB)
Ambient conditions
Degree of protection (IP) IP66 (using the corresponding A-SEW-...P-W flat gasket)
IP67 (using the corresponding A-SEW-...P-W flat gasket)
IP68 (using the corresponding A-SEW-...P-W flat gasket)
Ambient temperature (operation) -60 °C ... 130 °C (static)
General
Note with seal for conductor outer and inner jacket
Cable gland material Stainless steel 316L
Seal material EPDM
Cable seal material EPDM
Thread type connection side M63 x 1.5
Color silver
Impact energy 20.00 J
Assembly instructions With integrated grounding cones, sealed to IP66/IP67/IP68 thanks to the use of the A-SEW-63-P-W flat gasket (item 1411288)
Connection
Standard...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-EDSWU-M63-L66L-STES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.