

INDUSTRIAL COMPONENT DATA

G-ESS-M63-L66L-STES-S 1411087 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-ESS-M63-L66L-STES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-ESS-M63-L66L-STES-S
Catalog number	1411087
Category	Cable gland
Minimum order	2 Pcs
Document ID	EO-8BE1B2D0C6
Generated	2026-08-05

Product Overview

Cable gland

Cable gland, screwed connection material: 316L stainless steel, application: Ex, cable outer diameter 47.2 mm ... 56 mm, shielding: no, connection thread: M63 x 1.5, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1411087

Packing unit 2 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 556 (C-3-2017)

GTIN 4046356922005

Weight per Piece (excluding packing) 366.300 g

Custom tariff number 73182900

Country of origin GB (United Kingdom)

Dimensions

Length 45 mm

Thread pitch 1.5 mm

Wrench size, union nut 75 mm

Wrench size, support 75 mm

Hexagon angular dimension 82.5 mm

Length of the connecting thread 15 mm

External cable diameter 47.2 mm ... 56 mm

Cable types that can be used for unarmored cables

Ambient conditions

Degree of protection (IP) IP66 (using the corresponding A-SEW-...P-W flat gasket)

IP67 (using the corresponding A-SEW-...P-W flat gasket)

IP68 (using the corresponding A-SEW-...P-W flat gasket)

Ambient temperature (operation) -60 °C ... 130 °C (static)

General

Material Stainless steel 316L

Cable gland material Stainless steel 316L

Cable seal material EPDM

Thread type connection side M63 x 1.5

Color silver

Impact energy 20.00 J

Assembly instructions Sealed to IP66/IP67/IP68 thanks to the use of the A-SEW-63-P-W flat gasket (item 1411288)

Standards/specifications EN 60079-0, -1, -7, -15, -31

IEC 60079-0, -1, -7, -15, -31

EN 50262

BS 6121: Part 1:1989

IEC 62444

Manufacturer CMP

Manufacturer product number 63A2F1RA4

Manufacturer Designation 63 A2F S. STEEL GLAND

Suited for EX-applications yes

Standards and Regulations

Standards/regulations EN 60079-0, -1, -7, -15, -31

IEC 60079-0, -1, -7, -15, -31

EN 50262

BS 6121: Part....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-ESS-M63-L66L-STES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.