

INDUSTRIAL COMPONENT DATA

WP-GA HF IP66 M20 BK 3240926 PHOENIX CONTACT Screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-GA HF IP66 M20 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WP-GA HF IP66 M20 BK
Catalog number	3240926
Category	Cable gland
Minimum order	50 Pcs
Document ID	EO-9BD046D5B2
Generated	2026-08-03

Product Overview

Screw connection
Cable gland, metric thread, IP66 degree of protection, angled

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataProduct propertiesProduct type Corrugated pipe screw connection
Application Cable gland
Type of the screw connection Conduit adapter
Type Outer thread
Cable outlet angled
Thread type metric
Data management status
Article revision 00
DimensionsWidth 23 mm
Height 42 mm
Length 41.5 mm
Diameter 24.5 mm
Material specificationsMaterial PA 6
Flammability rating according to UL 94 V2

Material for screw connection	PA
Components free from silicone, halogen, and cadmium	
Cable/line	Halogen-free yes
Mechanical properties	Mechanical data
Type of the screw connection	Conduit adapter
Environmental and real-life conditions	Ambient conditions
Degree of protection	IP66
Ambient temperature (operation)	-40 °C ... 120 °C
ETIM for 3240926 Flexible conduit systems	(EC001178)
Feature Name	
Feature Value	
Nominal diameter (EF005114)	
15.8 mm	
Nominal size in inch (EF005462)	
Other	
Degree of protection (IP) (EF005474)	
IP66	
Revolving thread (EF001757)	
No	
Type of connection (EF000064)	
Other	
Thread connection size (EF007834)	
Other	
Thread length (EF000368)	
13 mm	
One-piece (EF001774)	
No	
With integrated holder (EF007952)	
No	
Material screw gland (EF008122)	
Polyamide (PA)	
Max. outer diameter hose (EF002504)	
15.8 mm	
Total height (EF001761)	
41.5 mm	
Total length (EF000369)	
41.5 mm	
Colour (EF000007)	
Black	
Approved in combination with protective conduit according to DIN EN 61386-23	(EF008142)
No	
Approved in combination with protective conduit UR	(EF001763)
No	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-GA HF IP66 M20 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.