

**INDUSTRIAL COMPONENT DATA**

# WP-GA HF IP66 PG36 BK 3240922 PHOENIX CONTACT Screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-GA HF IP66 PG36 BK



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | WP-GA HF IP66 PG36 BK |
| Catalog number  | 3240922               |
| Category        | Cable gland           |
| Minimum order   | 10 Pcs                |
| Document ID     | EO-E0701551B0         |
| Generated       | 2026-08-03            |

## Product Overview

Screw connection  
Cable gland, Pg thread, IP66 degree of protection, angled

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Industrial plug-in connectors/interfaces

## Additional Product Information

Technical dataProduct propertiesProduct type Corrugated pipe screw connection  
Application Cable gland  
Type Outer thread  
Cable outlet angled  
Thread type Pg  
Data management status  
Article revision 00  
DimensionsWidth 52 mm  
Height 83 mm  
Length 72 mm  
Diameter 51.5 mm  
Material specificationsMaterial PA 6  
Flammability rating according to UL 94 V2  
Material for screw connection PA

Components free from silicone, halogen, and cadmium

Cable/lineHalogen-free yes

Environmental and real-life conditionsAmbient conditions

Degree of protection IP66

Ambient temperature (operation) -40 °C ... 120 °C

ETIM for 3240922 Flexible conduit systems (EC001178)

Feature Name

Feature Value

Nominal diameter (EF005114)

42.5 mm

Nominal size in inch (EF005462)

Other

Degree of protection (IP) (EF005474)

IP66

Revolving thread (EF001757)

No

Type of connection (EF000064)

Other

Thread connection size (EF007834)

PG36

Thread length (EF000368)

15 mm

One-piece (EF001774)

No

With integrated holder (EF007952)

No

Material screw gland (EF008122)

Polyamide (PA)

Max. outer diameter hose (EF002504)

42.5 mm

Total height (EF001761)

72 mm

Total length (EF000369)

72 mm

Colour (EF000007)

Black

Approved in combination with protective conduit according to DIN EN 61386-23 (EF008142)

No

Approved in combination with protective conduit UR (EF001763)

No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-GA HF IP66 PG36 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.