

INDUSTRIAL COMPONENT DATA

US-WMTB (29X8) BU CUS 0830016 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-WMTB (29X8) BU CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-WMTB (29X8) BU CUS
Catalog number	0830016
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-D9CF3D2C6B
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, available: per card, blue, labelled according to customer specifications, mounting type: Mounting with cable tie, cable diameter: > 13 mm, usable area: 29x8mm, Number of individual indexes: 24

Cable marker, Card, available: per card, blue, labelled according to customer specifications, mounting type: Mounting with cable tie, cable diameter: > 13 mm, Number of individual indexes: 24, text field height: 8 mm, text field width: 29 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830016

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 191 (C-5-2013)

GTIN 4046356613552

Weight per Piece (excluding packing) 12.310 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 29 mm

Width (a) 16 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 80 °C

Recommended storage conditions 10-30 °C / 40-70 % relative humidity. Storage in the original packaging is recommended prior to processing.

General

Color blue

Type Card form

Components Silicone-free

Flammability rating according to UL 94 V0

Material PVC

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 24

Number of individual labels per row 6

Printability Thermal transfer

Device 5146464 THERMOMARK CARD

Ink ribbon 5146451 THERMOMARK CARD-US-MAG1

0801371 THERMOMARK-RIBBON 110-TC

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification following DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting ty...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-WMTB (29X8) BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.