

INDUSTRIAL COMPONENT DATA

US-WMTB (29X8) CUS 0830011 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-WMTB (29X8) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-WMTB (29X8) CUS
Catalog number	0830011
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-7716DF0563
Generated	2026-08-04

Product Overview

Cable marker

Cable marker, available: per card, white, labeled according to customer specifications, mounting class: Mounting with cable tie, cable diameter: > 13 mm, usable surface: 29x8mm, Number of individual indexes: 24

Cable marker, Card, can be ordered: by card, white, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 13 mm, Number of individual labels: 24, text field height: 8 mm, text field width: 29 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker

Type Card form

Data management status

Article revision 01

Marking

Number of individual labels 24

Number of individual labels per row 6

Identification technology Thermal transfer for sheets and cards

MountingMounting type Assembly with cable ties

Material specificationsColor white (RAL 9010)

Material PVC

Flammability rating according to UL 94 V0

Components Silicone-free

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -30 °C ... 80 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 %

Shelf life 12 months

Dimensions Width 16 mm

Text field width 29.00 mm

Text field height 8.00 mm

Length 29 mm

External dimensions

Outside diameter > 13 mm ... 136 mm

Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-WMTB (29X8) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.