

INDUSTRIAL COMPONENT DATA

UCT-WMTBA (40X17) CUS 1014092 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-WMTBA (40X17) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-WMTBA (40X17) CUS
Catalog number	1014092
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-4FA325D542
Generated	2026-08-01

Product Overview

Cable marker

Cable marker, available: by mats, white, labeled according to customer specifications, mounting class: Mounting with cable tie, cable diameter: > 6 mm, usable area: 40x17mm, Number of individual indexes: 3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1014092

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 271 (NTK-2014)

GTIN 4046356781442

Weight per Piece (excluding packing) 10.000 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 40 mm

Width (a) 17 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

General

Color white

Type Card form

Components free from silicone, halogen, and cadmium

Flammability rating according to UL 94 V0

Material PC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 3

Number of individual labels per row 1

Printability Thermal transfer

UV LED technology

Device 5146464 THERMOMARK CARD

5147999 BLUEMARK CLED

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type Assembly with cable binders

Result Test passed

Oxygen index (DIN EN ISO 4589-2) 32.4 %

R22 HL 1 - HL 3

R23 HL 1 - HL 3

R24 HL 1 - HL 3

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-WMTBA (40X17) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.