

INDUSTRIAL COMPONENT DATA

UCT-WMTBA (40X17) YE CUS 1014093 PHOENIX CONTACT

Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-WMTBA (40X17) YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-WMTBA (40X17) YE CUS
Catalog number	1014093
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-7DC486F2A9
Generated	2026-08-04

Product Overview

Cable marker

Cable marker, available: by mats, yellow, labelled according to customer specifications, mounting type: Mounting with cable tie, cable diameter: > 6 mm, usable surface: 40x17mm, Number of individual indexes: 3

Cable marker, Board, to order: as a board, yellow, printed according to customer specifications, Mounting type: Mounting with clamp, cable diameter: > 6 mm, Number of labels: 3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1014093

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 271 (NTK-2014)

GTIN 4046356781459

Weight per Piece (excluding packing) 9.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 40 mm

Width (a) 17 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
General
Color yellow
Type Card form
Components free from silicone, halogen, and cadmium
Flammability rating according to UL 94 V0
Material PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 3
Number of individual labels per row 1
Printability Thermal transfer
UV LED technology
Device 5146464 THERMOMARK CARD
5147999 BLUEMARK CLED
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Assembly with cable binders
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 32.4 %
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-WMTBA (40X17) YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.