

INDUSTRIAL COMPONENT DATA

LS-WMTB-V4A (100X15) CUS 0831805 PHOENIX CONTACT

Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-V4A (100X15) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	LS-WMTB-V4A (100X15) CUS
Catalog number	0831805
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-3A3A17CFFD
Generated	2026-08-04

Product Overview

Cable marker

Cable marker, Stainless steel plate, available: per piece, silver, labelled according to customer specifications, mounting class: Mounting with cable tie, cable diameter: > 4.6 mm, useful area: 100 x 15 mm, Number of individual indexes: 8

Cable marker, Stainless steel label, can be ordered: Piece, silver, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 4.6 mm, Number of individual labels: 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker

Type Card form

Data management status

Article revision 04

Marking

Number of individual labels 8

Identification technology Direct laser marking

MountingMounting type Assembly with cable ties

Material specificationsColor silver

Material V4A

Components free from silicone, halogen, and cadmium

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

Test for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Specification IEC 60068-2-2:2007-07

Result Test passed

Duration 240 h

Temperature for testing 350 °C

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 225 °C (250 °C) Test passed

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-1):2011-07

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Sodium hydroxide 0.1 mol/l

[CAS No. 1310-73-2] Test passed

Ethanol (99 %)

[CAS No. 64-17-5] Test passed

Acetone (99....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-V4A (100X15) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.