

INDUSTRIAL COMPONENT DATA

LS-WMTB-V4A (D25) CUS 0831806 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-V4A (D25) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	LS-WMTB-V4A (D25) CUS
Catalog number	0831806
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-4650B810DC
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, Stainless steel plate, available: per piece, silver, labelled according to customer specifications, mounting class: Mounting with cable tie, cable diameter: > 2.9 mm, usable area: d 25 mm, Number of individual indexes: 30

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0831806

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 249 (NTK-2014)

GTIN 4046356930154

Weight per Piece (excluding packing) 69.500 g

Custom tariff number 73269098

Country of origin DE (Germany)

Dimensions

Length (b) 25 mm

Width (a) 25 mm

Material thickness (g) 0.50 mm

Ambient conditions

Ambient temperature (operation) -80 °C ... 400 °C

General

Color silver

Type Card form

Components free from silicone, halogen, and cadmium

Material V4A

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 30

Printability Direct laser marking

Device 0831831 TOPMARK LASER

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO₂ test specification following DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type Assembly with cable binders

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss 7.027400401eCl@ss 8.027400401eCl@ss 9.027400401

ETIM....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-V4A (D25) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.