

INDUSTRIAL COMPONENT DATA

WML 3 (13X10)A4 CUS 0830699 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 3 (13X10)A4 CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 3 (13X10)A4 CUS
Catalog number	0830699
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-951032F3F7
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, available: Elbow, white, labeled according to customer's instructions, mounting class: glued, cable diameter: <= 3 mm, usable surface: 13 x 10 mm, Number of individual indices: 156

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830699

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 193 (C-5-2013)

GTIN 4046356718837

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 19 mm

Width (a) 13 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color white

Base element material Vinyl film

Type Label

Components Free from halogen and cadmium

Material Polyester

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 156

Number of individual labels per row 12

Adhesive Acrylic

Printability Office printing systems

Plotter

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 4.024190218eCl@ss 4.124190218eCl@ss 5.027141137eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss
7.027400401eCl@ss 8.027400401eCl@ss 9.027400401

ETIM 3.0EC000761ETIM 4.0EC001530ETIM 5.0EC001530ETIM 6.0EC001530

UNSP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 3 (13X10)A4 CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.