

INDUSTRIAL COMPONENT DATA

WML 22 (35X25)A4 YE CUS 0830708 PHOENIX CONTACT

Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 22 (35X25)A4 YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 22 (35X25)A4 YE CUS
Catalog number	0830708
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-B3062E6232
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, available: Elbow, yellow, labelled according to customer specifications, mounting class: glued, cable diameter range: 8 ... 21.3 mm, cable diameter: <= 21.3 mm, usable area: 35x25mm, Number of individual indexes: 15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

Additional Product Information

Key Commercial Data

Orderkey 0830708

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 193 (C-5-2013)

GTIN 4046356718929

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 92.25 mm

Width (a) 35 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color yellow

Base element material Vinyl film

Type Label

Components Free from halogen and cadmium

Material Polyester

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 15

Number of individual labels per row 5

Adhesive Acrylic

Printability Office printing systems

Plotter

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 4.024190218eCl@ss 4.124190218eCl@ss 5.027141137eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss
7.027400401eCl@ss 8.027400401eCl@ss 9.027400401

ETIM 3.0EC000761ETIM 4.0EC001530ETIM 5.0EC001530ETIM 6.0EC001530

UN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 22 (35X25)A4 YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.