

## INDUSTRIAL COMPONENT DATA

# KMK HP (60X15) 0830722 PHOENIX CONTACT Cable marker carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: KMK HP (60X15)



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | KMK HP (60X15)                  |
| Catalog number  | 0830722                         |
| Category        | Mounting for labelling material |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-FE074A28D5                   |
| Generated       | 2026-08-04                      |

## Product Overview

Cable marker carrier

Cable marker bracket, transparent, unlabeled, mounting class: Mounting with cable ties, cable diameter:  $\geq 9$  mm, usable surface: 60 x 15 mm

Cable marker carrier, transparent, unlabeled, mounting type: Assembly with cable ties, cable diameter:  $\geq 9$  mm, text field height: 15 mm, text field width: 60 mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Marker carrier cable

Area of application Railway industry

Type Mounting set

Data management status

Article revision 01

DimensionsWidth 15 mm

Text field width 60.00 mm

Height 60 mm

Text field height 15.00 mm

Length 60 mm

External dimensions

Outside diameter 9 mm ... 50 mm

Material specificationsColor transparent

Material PC

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Components halogen-free

Cable/lineExternal cable diameter  $\geq 9.00$  mm

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03

Result Test passed

Test duration 96 h

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 125 °C (150 °C) Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Ethanol (99 %)

[CAS No. 64-17-5] Test passed

Diesel

[CAS No. 68476-34-6] Test passed

IRM 901 Test passed

IRM 902 Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification DIN 50018:2013-05

Result Test passed

Climate level AHT 1.0 S

Cycles 2

Salt spray test

Specification DIN EN 60068-2-11:2000-02

Result Test passed

Test duration 96 h

High pressure test

Specification IEC 60529:20...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / KMK HP (60X15) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.