

INDUSTRIAL COMPONENT DATA

KMK UV (40X17) 1014109 PHOENIX CONTACT Cable marker carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: KMK UV (40X17)



Manufacturer	PHOENIX CONTACT
MPN / Reference	KMK UV (40X17)
Catalog number	1014109
Category	Mounting for labelling material
Minimum order	50 Pcs
Document ID	EO-DE75628EF0
Generated	2026-08-02

Product Overview

Cable marker carrier

Cable marker holder, transparent, unlabeled, mounting class: Mounting with cable tie, cable diameter: ≥ 9 mm, usable surface: 40x17mm

Cable marker carrier, transparent, unlabeled, mounting type: Assembly with cable ties, cable diameter: ≥ 9 mm, text field height: 17 mm, text field width: 40 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Marker carrier cable

Area of application Outdoors

Type Mounting set

Data management status

Article revision 02

DimensionsWidth 17 mm

Text field width 40.00 mm

Height 40 mm

Text field height 17.00 mm

Length 40 mm

External dimensions

Outside diameter 9 mm ... 50 mm

Material specificationsColor transparent

Material PA

Flammability rating according to UL 94 HB

Components halogen-free

UV Exposure and Water Immersion according to UL 746C f1

Cable/lineExternal cable diameter ≥ 9.00 mm

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 30000 h

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 100 °C (121 °C) Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Sodium hydroxide 0.1 mol/l

[CAS No. 1310-73-2] Test passed

Acetone (99 %)

[CAS No. 67-64-1] Test passed

Diesel

[CAS No. 68476-34-6] Test passed

IRM 901 Test passed

IRM 902 Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification DIN 50018:2013-05

Result Test passed

Climate level AHT 1.0 S

Cycles 2

Salt spray test

Specification DIN EN 60068-2-11:2000-02

Result Test passed

Test duration 96 h

High pressure test

Specification IEC 60529:2001-02

Result Test passed

Ambient conditions

Ambient temperature (operation) -40...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / KMK UV (40X17) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.