

INDUSTRIAL COMPONENT DATA

US-WML 14 (25X19) 0800473 PHOENIX CONTACT Cable marker label

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-WML 14 (25X19)



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-WML 14 (25X19)
Catalog number	0800473
Category	Cable coding system
Minimum order	10 Pcs
Document ID	EO-7071491846
Generated	2026-08-03

Product Overview

Cable marker label

Cable marker label, Card, white, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: glued, cable diameter range: 6.1 ... 14.2 mm, cable diameter: <= 14.2 mm, usable area: 25x19mm, Number of individual indexes: 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0800473

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 223 (C-3-2017)

GTIN 4046356607056

Weight per Piece (excluding packing) 5.150 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 25.4 mm

Width (a) 63.5 mm

Ambient conditions

Ambient temperature (operation) -50 °C ... 110 °C

General

Color white

Base element material Vinyl film

Type Label

Components Silicone-free

Material PVC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 8

Number of individual labels per row 4

Adhesive Acrylic

Printability Thermal transfer

Device 5146464 THERMOMARK CARD

5146451 THERMOMARK CARD-US-MAG1

Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN ISO 9227:2012-09

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Burning behaviour self-extinguishing

Foil strength 0.06 mm

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 4.0 24190219 eCl@ss 4.1 24190219 eCl@ss 5.0 27141137 eCl@ss 5.1 27400400...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-WML 14 (25X19) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.