

INDUSTRIAL COMPONENT DATA

WML 7,5 (25X13)A4 0830691 PHOENIX CONTACT Cable marker label

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 7,5 (25X13)A4



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 7,5 (25X13)A4
Catalog number	0830691
Category	Cable coding system
Minimum order	10 Pcs
Document ID	EO-17CC2DCBB4
Generated	2026-08-05

Product Overview

Cable marker label

Cable marker label, Elbow, white, unlabeled, labelable with: Office printing systems, CMS-P1-PLOTTER, PLOTMARK, mounting class: glued, cable diameter range: 4 ... 7.6 mm, cable diameter: <= 7.6 mm, usable area: 25x13mm, Number of individual indexes: 49

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830691

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 224 (C-3-2017)

GTIN 4046356718769

Weight per Piece (excluding packing) 15.280 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 31.75 mm

Width (a) 25 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Note Print image may vary depending on laser printer

Color white

Base element material Vinyl film

Type Label

Components free from silicone, halogen, and cadmium

Material Polyester

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 49

Number of individual labels per row 7

Adhesive Acrylic

Printability Office printing systems

Plotter

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027149103eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss

7.027400401eCl@ss 8.027400401eCl@ss 9.027400401

ETIM 3.0EC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 7,5 (25X13)A4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.