

INDUSTRIAL COMPONENT DATA

WML-RFID/HF 14 (25X19)R 0803386 PHOENIX CONTACT

Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML-RFID/HF 14 (25X19)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML-RFID/HF 14 (25X19)R
Catalog number	0803386
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-F7FA1E7BA9
Generated	2026-08-05

Product Overview

Cable marker

Cable marker label with RFID-HF transponder, roll, white, unlabeled, labelable with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, mounting type: adhesive, cable diameter: min. 9 mm, cable diameter: max. 14 mm, usable area: 25 x 19 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0803386

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 225 (C-3-2017)

GTIN 4055626047751

Weight per Piece (excluding packing) 499.000 g

Custom tariff number 85235200

Country of origin DE (Germany)

Dimensions

Length (b) 63 mm

Width (a) 25 mm

Cable diameter 6 mm ... 14 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Recommended storage conditions 20°C/50% relative humidity. Storage in the original packaging is recommended.

General

Color white

Base element material PVC

Type Label

Components Free from silicone and cadmium

Material PVC

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 750

Number of individual labels per row 1

Adhesive Acrylic

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 5.1 27400400 eCl@ss 6.0 27400400 eCl@ss 7.0 2740040...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML-RFID/HF 14 (25X19)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.