


INDUSTRIAL COMPONENT DATA

UC-WMT (12X4) GN 0823601 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMT (12X4) GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-WMT (12X4) GN
Catalog number	0823601
Category	Cable coding system
Minimum order	10 Pcs
Document ID	EO-7EDF9DB237
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, Mat, green, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting class: introduce, cable diameter range: 0.6 ... 10 mm, usable area: 12 x 4 mm, Number of individual indexes: 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data

Orderkey 0823601

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 210 (C-3-2017)

GTIN 4046356333368

Weight per Piece (excluding packing) 9.330 g

Custom tariff number 39269097

Country of origin PL (Poland)

Dimensions

Length (b) 4 mm

Width (a) 12 mm

Cable diameter 0.6 mm ... 10 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color green

Base element material PA

Type Card form

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 32

Number of individual labels per row 8

Printability UV LED technology

Device 5147999 BLUEMARK CLED

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type insert

Result Test passed

Oxygen index (DIN EN ISO 4589-2) 28,2%

Class I 3

Class F 2

R22 HL 1 - HL 2

R23 HL 1 - HL 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMT (12X4) GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.