


INDUSTRIAL COMPONENT DATA

UC-WMTBA (60X11) YE CUS 0824879 PHOENIX CONTACT

Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMTBA (60X11) YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-WMTBA (60X11) YE CUS
Catalog number	0824879
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-657B7488F8
Generated	2026-07-27

Product Overview

Cable marker

Cable marker, available: by mats, yellow, labeled according to customer's instructions, mounting class: Mounting with cable ties, cable diameter: > 6 mm, usable surface: 60 x 11 mm, Number of individual indexes: 4

Cable marker, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 6 mm, Number of individual labels: 4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker

Type Card form

Data management status

Article revision 02

Marking

Number of individual labels 4

Number of individual labels per row 1

Identification technology UV LED technology

MountingMounting type Assembly with cable ties

Material specificationsRoHS compliant yes

Color yellow (RAL 1018)

Material PA

Flammability rating according to UL 94 V2

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 120 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 2

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 2

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 2

Components free from silicone and halogen

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 %

Dimensions Width 16.6 mm

Length 60 mm

External dimensions

Outside diameter > 6 mm ... 136 mm

Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMTBA (60X11) YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.