


INDUSTRIAL COMPONENT DATA

US-WMTB (24X5) OG 0829321 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-WMTB (24X5) OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-WMTB (24X5) OG
Catalog number	0829321
Category	Cable coding system
Minimum order	10 Pcs
Document ID	EO-505C664443
Generated	2026-07-29

Product Overview

Cable marker

Cable marker, Card, orange, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: Mounting with cable tie, cable diameter: > 13 mm, useful surface: 24x5mm, Number of individual indexes: 35

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0829321

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 222 (C-3-2017)

GTIN 4046356613293

Weight per Piece (excluding packing) 12.780 g

Custom tariff number 39204910

Country of origin DE (Germany)

Dimensions

Length (b) 24 mm

Width (a) 14 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 80 °C

Recommended storage conditions 10-30 °C / 40-70 % relative humidity. Storage in the original packaging is recommended prior to processing.

General

Color orange

Type Card form

Components Silicone-free

Flammability rating according to UL 94 V0

Material PVC

PVC

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 35

Number of individual labels per row 7

Printability Thermal transfer

Device 5146464 THERMOMARK CARD

Ink ribbon 5146451 THERMOMARK CARD-US-MAG1

0801371 THERMOMARK-RIBBON 110-TC

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification following DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Re...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-WMTB (24X5) OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.