


INDUSTRIAL COMPONENT DATA

US-WMTB (29X8) GN 0829332 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-WMTB (29X8) GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-WMTB (29X8) GN
Catalog number	0829332
Category	Cable coding system
Minimum order	10 Pcs
Document ID	EO-2875D730DF
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, Card, green, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: Mounting with cable tie, cable diameter: > 13 mm, useful surface: 29x8mm, Number of individual indexes: 24

Cable marker, Card, green, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: Assembly with cable ties, cable diameter: > 13 mm, Number of individual labels: 24, text field height: 8 mm, text field width: 29 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Card form

Data management status

Article revision 00

Marking

Number of individual labels 24

Number of individual labels per row 6

Identification technology Thermal transfer for sheets and cards

DimensionsWidth 16 mm

Text field width 29.00 mm

Text field height 8.00 mm

Length 29 mm

External dimensions

Outside diameter > 13 mm ... 136 mm

Material specificationsColor green (RAL 6021)

Material PVC

Flammability rating according to UL 94 V0

Components Silicone-free

Cable/lineExternal cable diameter > 13.00 mm

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-1):2011-07

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification DIN 50018:2013-05

Result Test passed

Climate level AHT 1.0 S

Cycles 2

Salt spray test

Specification DIN EN 60068-2-11:2000-02

Result Test passed

Ambient conditions

Ambient temperature (operation) -30 °C ... 80 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommend...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-WMTB (29X8) GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.