

INDUSTRIAL COMPONENT DATA

WML 6 (13X13)R CUS 0824886 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 6 (13X13)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 6 (13X13)R CUS
Catalog number	0824886
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-0EE9DBE26B
Generated	2026-08-02

Product Overview

Cable marker

Cable marker, available: by lines, white, labelled according to customer specifications, mounting class: glued, cable diameter range: 4 ... 6.1 mm, cable diameter: <= 6.1 mm, usable area: 13x13mm

Cable marker, can be ordered: by line, white, labeled according to customer specifications, mounting type: adhesive, cable diameter range: 4 ... 6.1 mm, cable diameter: <= 6.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker

Type Label

Data management status

Article revision 01

Marking

Number of individual labels per row 7

MountingMounting type adhesive

Material specificationsFoil strength 80 µm

Adhesive strength 21 µm

Adhesive Acrylic

Color white (RAL 9010)

Material PVC

Components Silicone-free

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

Test for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 100 °C (121 °C) Test passed

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-01):2020-03

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Sodium hydroxide 0.1 mol/l

[CAS No. 1310-73-2] Test passed

Ethanol (99 %)

[CAS No. 64-17-5] Test passed

Acetone (99 %)

[CAS No. 67-64-1] Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Sodium hydroxide 0.1 mo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 6 (13X13)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.