

INDUSTRIAL COMPONENT DATA

WML 7,5 (25X13)R CUS 0824888 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 7,5 (25X13)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 7,5 (25X13)R CUS
Catalog number	0824888
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-ED5CD4D41A
Generated	2026-07-29

Product Overview

Cable marker

Cable marker, available: by lines, white, labelled according to customer specifications, mounting class: glued, cable diameter range: 4 ... 7.6 mm, cable diameter: <= 7.6 mm, usable area: 25x13mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0824888

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 195 (C-5-2013)

GTIN 4046356358118

Weight per Piece (excluding packing) 1.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 36.5 mm

Width (a) 25.4 mm

Ambient conditions

Ambient temperature (operation) -50 °C ... 110 °C

Recommended storage conditions 23 °C / 50% relative humidity. Storage in poly bags is recommended prior to processing.

General

Color white

Base element material Vinyl film

Type Label

Components Silicone-free

Material PVC

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels per row 3

Adhesive Acrylic

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146257 THERMOMARK S1.1

5146231 THERMOMARK X1.2

Ink ribbon 5145384 THERMOMARK-RIBBON 110

0829544 THERMOMARK-RIBBON 110 BU

0829542 THERMOMARK-RIBBON 110 GN

0829543 THERMOMARK-RIBBON 110 RD

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 7,5 (25X13)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.