

INDUSTRIAL COMPONENT DATA

WMTB (35X15)R 0817316 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB (35X15)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB (35X15)R
Catalog number	0817316
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-04311D8E45
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, Roll, white, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: Mounting with cable tie, cable diameter range: 6 ... 136 mm, cable diameter: ≥ 6 mm, usable area: 35 x 15 mm, number of individual indexes: 1700
Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: Assembly with cable ties, cable diameter range: 6 ... 136 mm, cable diameter: ≥ 6 mm, Number of individual labels: 1700, text field height: 15 mm, text field width: 35 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Roll

Data management status

Article revision 03

Marking

Number of individual labels 1700

Number of individual labels per row 2

Identification technology Thermal transfer for rolls

DimensionsWidth 15 mm

Text field width 35.00 mm
Text field height 15.00 mm
Length 48 mm
External dimensions
Outside diameter 0.5 mm ... 136 mm
Material specificationsFoil strength 175 µm
Color white (RAL 9010)
Material Polyester
Components free from silicone and halogen
Cable/lineExternal cable diameter >= 6.00 mm
6 mm ... 136 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification EN ISO 1518-1:2023 (following)
Requirements >= 5 N
Result Test passed
TesaFilm test
Specification DIN EN ISO 2409:2020-12 (following)
Result Test passed
UV resistance
Specification DIN EN ISO 2409:2020-12 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 150 °C (180 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Test passed
Ethanol (99 %)
[CAS No. 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB (35X15)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.