

INDUSTRIAL COMPONENT DATA

WMTB HF (55X15)R YE CUS 0830416 PHOENIX CONTACT

Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB HF (55X15)R YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB HF (55X15)R YE CUS
Catalog number	0830416
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-F567D890C5
Generated	2026-08-03

Product Overview

Cable marker

Cable marker, available: lined, yellow, labelled according to customer specifications, mounting type: Installation with cable tie, cable diameter: ≥ 6 mm, usable area: 55 x 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

Additional Product Information

Key Commercial Data

Orderkey 0830416

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 212 (C-5-2013)

GTIN 4046356716109

Weight per Piece (excluding packing) 1.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 55 mm

Width (a) 15 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 80 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color yellow

Type Roll

Components halogen-free

Flammability rating according to UL 94 V0

Material PUR

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 1000

Number of individual labels per row 1

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Note The information does not apply to the color fastness of the material.

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions IEC 61010-1:2010-06

Result Test passed

Marking mounting type Assembly with cable binders

Standards and Regulations

Wipe re...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB HF (55X15)R YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.