

INDUSTRIAL COMPONENT DATA

WMTB HF (55X15)R DBU 0802992 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB HF (55X15)R DBU



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB HF (55X15)R DBU
Catalog number	0802992
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-CFC8006D98
Generated	2026-08-05

Product Overview

Cable marker

Cable marker, Roll, dark blue, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: Mounting with cable ties, cable diameter: ≥ 6 mm, usable area: 55 x 15 mm, Number of individual indexes: 1000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0802992

Packing unit 1 pc

Catalog page Page 240 (C-3-2017)

GTIN 4046356891059

Weight per Piece (excluding packing) 1,243.000 g

Custom tariff number 39204910

Country of origin DK (Denmark)

Dimensions

Length (b) 55 mm

Width (a) 15 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 80 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color dark blue

Type Roll

Components halogen-free

Flammability rating according to UL 94 V0

Material PUR

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 1000

Number of individual labels per row 1

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

Ink ribbon 0802990 TM-RIBBON 110-WMTB HF WH

0802990 TM-RIBBON 110-WMTB HF WH

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Note The information does not apply to the color fastness of the material.

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions IEC 61010-1:2010-06

Result Test passed

Marking mounting type Assembly with cable binders

Standards and Regulations

Wipe res...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB HF (55X15)R DBU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.