

INDUSTRIAL COMPONENT DATA

WMTB HF (55X15)R RD 0803315 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB HF (55X15)R RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB HF (55X15)R RD
Catalog number	0803315
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-6333E10997
Generated	2026-08-04

Product Overview

Cable marker

Cable marker, Roll, red, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: Cable mounting, cable diameter: ≥ 6 mm, usable area: 55 x 15 mm, Number of individual indexes: 1000

Cable marker, Roll, red, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: Assembly with cable ties, cable diameter: ≥ 6 mm, Number of individual labels: 1000, text field height: 15 mm, text field width: 55 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Roll

Data management status

Article revision 00

Marking

Number of individual labels 1000

Number of individual labels per row 1

Identification technology Thermal transfer for rolls

DimensionsWidth 15 mm
Text field width 55.00 mm
Text field height 15.00 mm
Length 55 mm
External dimensions
Outside diameter 6 mm ... 136 mm
Material specificationsRoHS compliant yes
Color red (RAL 3001)
Material PUR
Flammability rating according to UL 94 V2 (0,75 mm Wandstärke)
Components halogen-free
Cable/lineExternal cable diameter ≥ 6.00 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements ≥ 5 N
Result Test passed
Tesa film test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 125 °C (150 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Test passed
Specifica...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB HF (55X15)R RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.