

INDUSTRIAL COMPONENT DATA

WML HF 7,5(25X13)R 0830816 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML HF 7,5(25X13)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML HF 7,5(25X13)R
Catalog number	0830816
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-B7A91D39E9
Generated	2026-08-04

Product Overview

Cable marker

Cable wrapping label, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting class: glued, cable diameter range: 4 ... 7.6 mm, cable diameter: <= 7.6 mm, usable area: 25x13mm, Number of individual indexes: 2100

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data

Orderkey 0830816

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 226 (C-3-2017)

GTIN 4046356800624

Weight per Piece (excluding packing) 587.700 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 36.5 mm

Width (a) 25.4 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

Recommended storage conditions 21°C/50% relative humidity. Storage in the original packaging is recommended prior to processing.

General

Color white

Base element material Vinyl film

Type Label

Components free from silicone and halogen

Material Polyethylene

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 2100

Number of individual labels per row 3

Adhesive Acrylic

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML HF 7,5(25X13)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.