

**INDUSTRIAL COMPONENT DATA**

# LS-WMTB-V4A (100X15) 0831519 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-V4A (100X15)



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | PHOENIX CONTACT      |
| MPN / Reference | LS-WMTB-V4A (100X15) |
| Catalog number  | 0831519              |
| Category        | Cable coding system  |
| Minimum order   | 5 Pcs                |
| Document ID     | EO-1D95C7458E        |
| Generated       | 2026-08-04           |

## Product Overview

Cable marker

Cable marker, Stainless steel plate, silver, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, mounting class: Mounting with cable tie, cable diameter: > 4.6 mm, useful surface: 100x15mm, Number of individual indices: 8

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0831519

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 197 (C-3-2017)

GTIN 4046356925297

Weight per Piece (excluding packing) 100.280 g

Custom tariff number 73269098

Country of origin CN (China)

Dimensions

Length (b) 118 mm

Width (a) 15 mm

Material thickness (g) 0.50 mm

Ambient conditions

Ambient temperature (operation) -80 °C ... 400 °C

General

Color silver

Type Card form

Components free from silicone, halogen, and cadmium

Material V4A

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 8

Printability Direct laser marking

Device 0831831 TOPMARK LASER

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO<sub>2</sub> test specification following DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type Assembly with cable binders

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss 7.027400401eCl@ss 8.027400401eCl@ss 9.027400401

ETIM 4.0EC0015...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-V4A (100X15) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.