

INDUSTRIAL COMPONENT DATA

WML-FLAG 6 (20X10)R 0830711 PHOENIX CONTACT Cable marking flags

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML-FLAG 6 (20X10)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML-FLAG 6 (20X10)R
Catalog number	0830711
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-6587C3B09D
Generated	2026-08-02

Product Overview

Cable marking flags

Cable wrapping label, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting class: glued, cable diameter: <= 6 mm, useful surface: 20x10mm, Number of individual indexes: 2500

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830711

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 227 (C-3-2017)

GTIN 4046356724555

Weight per Piece (excluding packing) 524.900 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 20 mm

Width (a) 10 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (assembly) > 5 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color white

Base element material Vinyl film

Type Label

Components free from silicone and halogen

Material Polyolefine

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 2500

Number of individual labels per row 1

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

0804501 THERMOMARK ROLLMASTER 300

0804663 THERMOMARK ROLLMASTER 600

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type adhesive

Standards and Regulations

Wipe resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML-FLAG 6 (20X10)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.