

**INDUSTRIAL COMPONENT DATA**

# CABLE-D15SUB/B/S/100/KONFEK/S 2302065 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: CABLE-D15SUB/B/S/100/KONFEK/S



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | CABLE-D15SUB/B/S/100/KONFEK/S |
| Catalog number  | 2302065                       |
| Category        | PLC connection cable          |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-2B7EE668B0                 |
| Generated       | 2026-07-31                    |

## Product Overview

**Cable**

Shielded ready-made round cable; Connection 1: Female connection D-SUB (1x 15-poles); connection 2: D-SUB male connector (1x 15-pole); Cable length: 1 m

Assembled shielded round cable; connection 1: D-SUB socket strip (1x 15-position); connection 2: D-SUB pin strip (1x 15-position); cable length: 1 m

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                             |
|--------------|---------------------------------------------|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |
|--------------|---------------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type System cable

Data management status

Article revision 05

Environmental and real-life conditionsAmbient conditions

Degree of protection IP20

Degree of protection (Installation location) >= IP54 (Installation location)

Ambient temperature (operation) -40 °C ... 70 °C (fixed installation)

-10 °C ... 70 °C (flexible installation)

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude <= 2000 m

Electrical propertiesOperating voltage (AC) <= 30 V AC

Operating voltage (DC)  $\leq 60$  V DC  
Nominal operating mode 100% operating factor  
Current (Per path)  $\leq 2$  A (Uncoiled, see derating)  
Cable/line Cable length 1 m  
15X0.25 [PVC]  
UL AWM Style 2464/1061  
Number of positions 15  
Shielded yes  
Cable type 15X0.25 [PVC]  
Conductor type Assembled shielded round cable  
Conductor structure signal line 14x 0.15 mm  
AWG signal line 24  
Conductor cross section 15x 0.25 mm<sup>2</sup>  
Wire diameter incl. insulation 1.2 mm  $\pm 0.05$  mm  
External cable diameter 7.90 mm  $\pm 0.5$  mm  
Outer sheath, material Semi-rigid PVC  
External sheath, color gray  
Conductor material Bare Cu litz wires  
Cable resistance  $\leq 80$   $\Omega$ /km (at 20 °C)  
Insulation resistance  $\geq 20$  M $\Omega$ \*km (at 20 °C)  
Smallest bending radius, fixed installation 67 mm  
Smallest bending radius, movable installation 126 mm  
Dynamic load capacity (bending) Max. bending cycles: 5000 (at a radius of  $\geq 15$ x outside diameter)  
Halogen-free no  
Flame resistance IEC 60332-1-2 (raw cable)  
VDE 0842, Part 332-1-2 (raw cable)  
IEC 60332-3-22 (raw cable)  
UL VW...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CABLE-D15SUB/B/S/100/KONFEK/S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.