

INDUSTRIAL COMPONENT DATA

SAC-12P-MR/ 1,5-35T SH SCO 1430080 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-12P-MR/ 1,5-35T SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-12P-MR/ 1,5-35T SH SCO
Catalog number	1430080
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-12C6694810
Generated	2026-08-02

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 12-pole, shielded, M12 angled connector, coding: A SPEEDCON, to free cable end, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1430080

Packing unit 1 pc

Catalog page Page 220 (C-2-2017)

GTIN 4046356322355

Weight per Piece (excluding packing) 153.200 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 1.5 m

Stripping length of the free conductor end 35 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 1.5 A

Rated voltage 30 V AC

30 V DC

Number of positions 12

Insulation resistance $\geq 10 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA 6.6

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flame resistance DIN VDE 0472 part 804, test type B

Resistance to oil DIN VDE 0472 Part 803, test type B

Other resistance Hydrolysis and microbe resistant as per VDE 0282 section 10

Flammability rating according to UL 94 V0

Cable

Cable type Black PUR/PVC twisted pair

Cable type (abbreviation) 35T

Cable abbreviation LSPYwC11Y

UL AWM style 20233 / 1061 (80°C/300 V)

Conductor cross section 12x 0.14 mm² (Signal line)

A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-12P-MR/ 1,5-35T SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.