

INDUSTRIAL COMPONENT DATA

SAC-12P-MR/ 1,5-PUR SCO 1430572 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-12P-MR/ 1,5-PUR SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-12P-MR/ 1,5-PUR SCO
Catalog number	1430572
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-EFCD00E505
Generated	2026-08-01

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 12-pole halogen-free, M12 angled connector, coding: A SPEEDCON, to free cable end, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1430572

Packing unit 1 pc

Catalog page Page 218 (C-2-2017)

GTIN 4046356456395

Weight per Piece (excluding packing) 112.600 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 1.5 m

Stripping length of the free conductor end 35 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 1.5 A
Rated voltage 30 V AC
30 V DC
Number of positions 12
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Resistance to oil DIN VDE 0472 Part 803, test type B
Other resistance Hydrolysis and microbe resistant as per VDE 0282 section 10
Flammability rating according to UL 94 V0
Cable
Conductor cross section $12 \times 0.14 \text{ mm}^2$ (Signal line)
AWG signal line 26
Conductor structure signal line $18 \times 0.10 \text{ mm}$
Core diameter including insulation $1 \text{ mm} \pm 0.05 \text{ mm}$ (Signal line)
Wire colors white, brown, green, yellow, gray, pink, blue...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-12P-MR/ 1,5-PUR SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.