

INDUSTRIAL COMPONENT DATA

SAC-3P- 1,5-PUR/A-1L-V 230V 1402985 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-1,5-PUR/A-1L-V 230V



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-1,5-PUR/A-1L-V 230V
Catalog number	1402985
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-76544E81CD
Generated	2026-08-04

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 3-pole halogen-free, free cable end, to Valve Connectors A, with 1 LED, connected with Varistor 230 V, cable length: 1.5 m

Sensor/actuator cable, 3-pole, halogen-free PUR, grayish black RAL 7021, free cable end, to Valve connectors A, with 1 LED, Circuit: Varistor 230 V, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1402985

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 238 (C-2-2017)

GTIN 4046356638371

Weight per Piece (excluding packing) 71.500 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1.5 m

Ambient conditions

Ambient temperature (operation) -20 °C ... 85 °C (valve plug)

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 230 V AC

230 V DC

Number of positions 3

Color handle area black

Insulation resistance $\geq 100 \text{ M}\Omega$

Standards/regulations Valve connector EN 175301-803

Status display 1 LED

Protective circuit/component Varistor 230 V

Overvoltage category III

Degree of pollution 3

Torque 0.6 Nm (Valve connector)

Material

Flammability rating according to UL 94 V0

Valve plug contact material CuSn

Valve plug contact surface material Sn

Valve plug contact insert material PA 6.6

Material housing valve plug TPU

Sealing material TPU (Seal molded)

Standards and Regulations

Standard designation Valve connector

Standards/regulations EN 175301-803

Flammability rating according to UL 94 V0

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549

Conductor cross section $3 \times 0.5 \text{ mm}^2$

AWG signal line 20

Conductor structure signal line $28 \times 0.15 \text{ mm}$

Core diameter including insulation $1.5 \text{ mm} \pm 0.05 \text{ mm}$ (Signal line)

Wire colors black 1, black 2, green/yellow

Overall twist 3 wires, twisted

External sheath, color black-gray RAL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-1,5-PUR/A-1L-V 230V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.