


INDUSTRIAL COMPONENT DATA

SAC-3P- 1,5-PUR/M 8FR SH 1521766 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-1,5-PUR/M 8FR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-1,5-PUR/M 8FR SH
Catalog number	1521766
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-3E5B14C5EA
Generated	2026-08-03

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, shielded, free cable end, to M8 angled connection female, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1521766

Packing unit 1 pc

Catalog page Page 199 (C-2-2017)

GTIN 4017918968755

Weight per Piece (excluding packing) 48.800 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1.5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M8 connector IEC 61076-2-104

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.2 Nm (M8 connectors)

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y-V1-C-V1-11Y

UL AWM style 20549

Conductor cross section $3 \times 0.25 \text{ mm}^2$ (Signal line)

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$

Core diameter including insulation $1.17 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)

Thickness, insulation $\geq \dots$

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-1,5-PUR/M 8FR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.