

INDUSTRIAL COMPONENT DATA

SAC-3P- 5,0-PUR/CI-1L-V 1443284 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-5,0-PUR/CI-1L-V



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-5,0-PUR/CI-1L-V
Catalog number	1443284
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-D5E721B774
Generated	2026-08-04

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 3-pole halogen-free, free cable end, to IC valve connectors (9.4mm), with 1 LED, connected with Varistor, cable length: 5 m

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Valve connector CI (9.4 mm), with 1 LED, Wiring: Varistor, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable with valve connector

Application Standard

Number of positions 3

No. of cable outlets 1

Shielded no

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0

Seal material TPU

Material housing valve plug TPU

Contact material CuSn
Valve plug contact insert material PA 6.6
Contact surface material Sn
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 24 V AC
24 V DC
Nominal current IN 4 A
Valve connector characteristics
Fixing screws M3 x 29
SignalingStatus display 1 LED
Status display present Yes
ConnectorConnection 1
Type free cable end
Connection 2
Type Valve connector CI (9.4 mm)
Number of positions 3
Material CuSn (Contact)
Sn (Contact surface)
PA 6.6 (Contact carriers)
TPU (Housing)
Cable/lineCable length 5 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 30 kg/km
UL AWM Style 20549
Number of positions 3
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 28x 0.15 mm
AWG signal line 20
Conductor cross section 3x 0.5 mm²
Wire diameter incl. insulation 1.5 mm $\pm 0.05 \text{ mm}$ (Signal line)
External cable diameter 4.50 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color black 1, black 2, green/yellow
Overall twist 3 wires, twisted
Max. conductor resistance 39....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-5,0-PUR/CI-1L-V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.