

INDUSTRIAL COMPONENT DATA

SAC-4P-2,0-186/FS SCO 1555648 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-2,0-186/FS SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-2,0-186/FS SCO
Catalog number	1555648
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-8719D398D9
Generated	2026-08-04

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 4-Pole, PUR, Grey-Black RAL 7021, Free Cable End, to Straight Connecting Female M12 SPEEDCON, Coding: A

Sensor/actuator cable, 4-position, PUR, black-gray RAL 7021, free cable end, on Socket straight M12 SPEEDCON, coding: A, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material for screw connection Zinc die-cast, nickel-plated

Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 250 V AC

250 V DC

Nominal current IN 4 A

Mechanical propertiesMechanical data

Insertion/withdrawal cycles ≥ 100

SignalingStatus display no

Status display present No

Connection dataConductor connection

Tightening torque 0.4 Nm

ConnectorConnection 1

Type free cable end

Connection 2

Type Socket straight M12 SPEEDCON

Number of positions 4

Locking type SPEEDCON

Coding type A

Cable/lineCable length 2 m

PUR POWER 0.75 mm² black [186]

Dimensional drawing

Cable weight 57 kg/km

UL AWM Style 20549 / 1061 (80°C/300 V)

Number of positions 4

Shielded no

Cable type PUR POWER 0.75 mm² black [186]

Conductor structure signal line 42x 0.15 mm

AWG signal line 18

Conductor cross section 4x 0.75 mm² (power line)

Wire diameter incl. insulation 1.75 mm $\pm 0.05 \text{ mm}$

External cable diameter 5.90 mm $\pm 0.15 \text{ mm}$

Outer sheath, material PUR

External sheath, color black-gray RAL 7021

Conductor material Bare Cu litz wires

Material wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-2,0-186/FS SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.