

**INDUSTRIAL COMPONENT DATA**

# SAC-4P-M12MS/ 1,5-PUR/M12FS P 1442858 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 1,5-PUR/M12FS P



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | SAC-4P-M12MS/ 1,5-PUR/M12FS P |
| Catalog number  | 1442858                       |
| Category        | Sensor-actuator patch cord    |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-77D5CF95AD                 |
| Generated       | 2026-08-02                    |

## Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, Straight connector M12, coding: A, to Straight female M12, coding: A, cable length: 1.5 m, with plastic knurling

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |
|--------------|-------------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1442858

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 132 (PC-2011)

GTIN 4046356535762

Weight per Piece (excluding packing) 50.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65  
IP67  
IP68  
General  
Rated current at 40°C 4 A  
Rated voltage 250 V AC  
250 V DC  
Number of positions 4  
Insulation resistance  $\geq 100 \text{ M}\Omega$   
Coding A - standard  
Standards/regulations M12 connector IEC 61076-2-101  
Status display No  
Protective circuit/component unwired  
Overvoltage category II  
Degree of pollution 3  
Insertion/withdrawal cycles  $\geq 100$   
Torque 0.4 Nm (M12 connector)  
Material  
Flammability rating according to UL 94 HB  
Contact material CuSn  
Contact surface material Ni/Au  
Contact carrier material TPU GF  
Material of grip body TPU, hardly inflammable, self-extinguishing  
Material, knurls Polyamide  
Sealing material NBR  
Standards and Regulations  
Standard designation M12 connector  
Standards/regulations IEC 61076-2-101  
Flammability rating according to UL 94 HB  
Cable  
Cable type PUR halogen-free black  
Cable type (abbreviation) PUR  
Cable abbreviation Li9Y11Y-HF  
UL AWM style 20549 / 10493 (80°C/300 V)  
Conductor cross section  $4 \times 0.34 \text{ mm}^2$   
AWG signal line 22  
Conductor structure signal line  $42 \times 0.10 \text{ mm}$   
Core diameter including insulation  $1.27 \text{ mm} \pm 0.02 \text{ mm}$   
Thickness, insulation  $\geq 0.21 \text{ mm}$   
Wire colors brown, white, bl...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 1,5-PUR/M12FS P with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.