


## INDUSTRIAL COMPONENT DATA

# SAC-4P-M12MS/ 1,5-PUR SH 1682715 PHOENIX CONTACT

## Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 1,5-PUR SH



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-4P-M12MS/ 1,5-PUR SH   |
| Catalog number  | 1682715                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-D83DB0AB1F              |
| Generated       | 2026-08-01                 |

### Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole halogen-free, shielded (Advanced Shielding Technology), Straight M12 connector, coding: A, to free cable end, cable length: 1.5 m

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Industrial Field Connectivity (IFC)

### Additional Product Information

Key Commercial Data

Orderkey 1682715

Packing unit 1 pc

Catalog page Page 205 (C-2-2017)

GTIN 4017918168995

Weight per Piece (excluding packing) 71.200 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1.5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Insulation resistance  $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles  $\geq 100$

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y-V1-C-V1-11Y

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section  $4 \times 0.34 \text{ mm}^2$  (Signal line)

AWG signal line 22

Conductor structure signal line  $42 \times 0.10 \text{ mm}$

Core diameter including insulation  $1.27 \text{ mm} \pm 0.02 \text{ mm}$  (Signal line)....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 1,5-PUR SH with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.