

**INDUSTRIAL COMPONENT DATA**

# SAC-4P-M12MS/3,0-600/FS SH HD 1403993 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/3,0-600/FS SH HD



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | SAC-4P-M12MS/3,0-600/FS SH HD |
| Catalog number  | 1403993                       |
| Category        | Sensor-actuator patch cord    |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-F99E95371F                 |
| Generated       | 2026-08-02                    |

## Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, halogen-free PP-EPDM, grey RAL 7035, shielded, M12 straight male connector, coding: A, to M12 straight connection female, coding: A, cable length: 3 m, Hygienic design, with stainless steel knurling

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |
|--------------|-------------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1403993

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 142 (C-4-2013)

GTIN 4046356677479

Weight per Piece (excluding packing) 148.600 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 3 m

Ambient conditions

Ambient temperature (operation) -40 °C ... 105 °C (Plug / socket)

Degree of protection IP65  
IP67  
IP68  
IP69K  
General  
Rated current at 40°C 4 A  
Rated voltage 48 V AC  
60 V DC  
Number of positions 4  
Insulation resistance  $\geq 100 \text{ M}\Omega$   
Coding A - standard  
Standards/regulations M12 connector IEC 61076-2-101  
Material conformance FDA 21 CFR 177.2600  
Status display No  
Protective circuit/component unwired  
Overvoltage category II  
Degree of pollution 3  
Insertion/withdrawal cycles  $\geq 100$   
Torque 0.4 Nm (M12 connector)  
Material  
Contact material CuSn  
Contact surface material Ni/Au  
Contact carrier material PP  
Material of grip body PP  
Material, knurls Stainless steel  
Sealing material FKM  
Standards and Regulations  
Standard designation M12 connector  
Standards/regulations IEC 61076-2-101  
Standard designation Material conformance  
Standards/regulations FDA 21 CFR 177.2600  
Cable  
Cable type Halogen-free PP gray shielded  
Cable type (abbreviation) 600  
Cable abbreviation Li9YV1-C-V1-9Y  
Conductor cross section  $4 \times 0.34 \text{ mm}^2$  (Signal line)  
AWG signal line 22  
Conductor structure signal line  $42 \times 0.10 \text{ mm}$   
Core diameter including insulation  $1.27 \text{ mm} \pm 0.02 \text{ mm}$  (Signal line)  
Thickness, insulation  $\geq 0.21 \text{ mm}$  (Core insulation)  
Wire...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/3,0-600/FS SH HD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.