

INDUSTRIAL COMPONENT DATA

SAC-4P-MS/ 1,0-186/FS SCO 1555703 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-MS/ 1,0-186/FS SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-MS/ 1,0-186/FS SCO
Catalog number	1555703
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-F8BEE04774
Generated	2026-08-03

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, PUR, grayish black RAL 7021, M12 SPEEDCON straight male connector, coding: A, to M12 SPEEDCON straight connection female, coding: A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1555703

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 440 (C-2-2017)

GTIN 4046356173704

Weight per Piece (excluding packing) 76.900 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Torque 0.4 Nm
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR POWER 0.75 mm² black
Cable type (abbreviation) 186
Cable abbreviation LiY11Y
UL AWM style 20549 / 1061 (80°C/300 V)
Conductor cross section 4x 0.75 mm² (power line)
AWG signal line 18
Conductor structure signal line 42x 0.15 mm
Core diameter including insulation 1.75 mm $\pm 0.05 \text{ mm}$
Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)
 $\geq 0.76 \text{ mm}$ (Outer cable sheath)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-MS/ 1,0-186/FS SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.