

INDUSTRIAL COMPONENT DATA

SAC- 5,0/0,2-116/2XB-1L-Z 1458266 PHOENIX CONTACT

Double valve connector cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5,0/0,2-116/2XB-1L-Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5,0/0,2-116/2XB-1L-Z
Catalog number	1458266
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-5935A994E1
Generated	2026-08-02

Product Overview

Double valve connector cable

Double Valve Connector Cable, 4-Pole, Free Cable End, to Valve Connectors B (10mm), with 1 LED, connected to Diode Z and Valve Connectors B (10mm), with 1 LED, connected to Diode Z, cable length: 5 m, distance from valve connector: 0.2 m

Double valve connector cable, 4-position, PUR/PVC, black, free cable end, on Valve connector B (10 mm), with 1 LED, Wiring: Z diode and Valve connector B (10 mm), with 1 LED, Wiring: Z diode, cable length: 5 m, valve connector spacing: 0.2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable with valve connector

Application Standard

Number of positions 4

No. of cable outlets 1

Shielded no

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material TPU
Material housing valve plug TPU
Contact material CuSn
Valve plug contact insert material PA 6.6
Contact surface material Sn
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 24 V AC
24 V DC
Nominal current IN 4 A
Valve connector characteristics
Fixing screws M3 x 29
Pulse power 40 W (at 100 μs square-wave pulse)
Terminal voltage 70 V (at 2 mA constant current)
Reverse voltage 50 V
Mechanical propertiesMechanical data
Insertion/withdrawal cycles 50
SignalingStatus display 1 LED
Status display present Yes
ConnectorConnection 1
Type free cable end
Connection 2
Type Valve connector B (10 mm)
Material CuSn (Contact)
Sn (Contact surface)
PA 6.6 (Contact carriers)
TPU (Housing)
Connection 3
Type Valve connector B (10 mm)
Material CuSn (Contact)
Sn (Contact surface)
PA 6.6 (Contact carriers)
TPU (Housing)
Cable/lineCable length 5 m
0.2 m
PUR/PVC, 0.75 mm², black [116]
Dimensional drawing
Cable weight 57 kg/km
UL AWM Style 20549
Number of positions 4
Shielded no
Cable type PUR/PVC, 0.75 mm², black [116]
Conductor structure signal line 24x 0.20 mm
AWG signal line 18
Conductor cross section 4x 0.75 mm²
Wire diameter incl. insulation 1.7 mm $\pm 0.05 \text{ mm}$...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5,0/0,2-116/2XB-1L-Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.