

INDUSTRIAL COMPONENT DATA

SAC-6P-M 8MR/10,0-PUR SH 1522370 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-6P-M 8MR/10,0-PUR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-6P-M 8MR/10,0-PUR SH
Catalog number	1522370
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-F6AF647E48
Generated	2026-08-02

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 6-pole halogen-free, shielded, M8 angled connector, coding: A, to free cable end, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1522370

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 212 (C-2-2017)

GTIN 4046356021135

Weight per Piece (excluding packing) 370.300 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 10 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
General
Rated current at 40°C 1.5 A
Rated voltage 30 V AC
30 V DC
Number of positions 6
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Torque 0.2 Nm (M8 connectors)
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Conductor cross section $6 \times 0.14 \text{ mm}^2$ (Signal line)
AWG signal line 26
Conductor structure signal line $18 \times 0.10 \text{ mm}$
Core diameter including insulation $1.05 \text{ mm} \pm 0.02 \text{ mm}$
Wire colors Brown, white, black, blue, gray, pink
External sheath, color bl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-6P-M 8MR/10,0-PUR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.