

## INDUSTRIAL COMPONENT DATA

# SAC-8P-M 8MS/ 0,6-PUR/M 8FS SH 1404134 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M 8MS/ 0,6-PUR/M 8FS SH



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SAC-8P-M 8MS/ 0,6-PUR/M 8FS SH |
| Catalog number  | 1404134                        |
| Category        | Sensor-actuator patch cord     |
| Minimum order   | 1 Pcs                          |
| Document ID     | EO-17F5D69B0A                  |
| Generated       | 2026-08-04                     |

## Product Overview

Sensor/actuator cable

Sensor/actuator cable, 8-pole halogen-free, shielded, M8 straight connector, encoding: A, to M8 straight female, cable length: 0.6 m

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Industrial Field Connectivity (IFC)

## Additional Product Information

Key Commercial Data

Orderkey 1404134

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 216 (C-2-2017)

GTIN 4046356680455

Weight per Piece (excluding packing) 43.600 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 0.6 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 1.5 A

Rated voltage 30 V AC

30 V DC

Number of positions 8

Insulation resistance  $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M8 connector IEC 61076-2-104

Status display No

Protective circuit/component unwired

Degree of pollution 3

Insertion/withdrawal cycles  $\geq 100$

Torque 0.2 Nm (M8 connectors)

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable abbreviation Li9YV1-C-V1-11Y

UL AWM style 20549

Conductor cross section  $8 \times 0.14 \text{ mm}^2$  (Signal line)

AWG signal line 26

Conductor structure signal line  $18 \times 0.10 \text{ mm}$

Core diameter including insulation  $1 \text{ mm} \pm 0.02 \text{ mm}$  (Signal line)

Thickness, insulation  $\geq 0.21 \text{ mm}$  (Signal line)

$\geq 0.38 \text{ mm}$  (Outer cable sheath)

Wire colors whi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M 8MS/ 0,6-PUR/M 8FS SH with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.