

## INDUSTRIAL COMPONENT DATA

# VS-M12FSBP-IP67/B-94C-LI/2,0 1413476 PHOENIX CONTACT

## Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-M12FSBP-IP67/B-94C-LI/2,0



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | VS-M12FSBP-IP67/B-94C-LI/2,0     |
| Catalog number  | 1413476                          |
| Category        | Patch cord copper (twisted pair) |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-79317AB6CF                    |
| Generated       | 2026-07-28                       |

### Product Overview

Network cable

Confected Ethernet cable, shielded, 4 pairs, AWG 26 suitable for supply chains (19 wires), RAL 5021 (aqua blue), female mount. incorp. M12, mont. Back/screwed wall c. M16 thread in connector. RJ45/IP67 male, black, Line, long. 2 m

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Field Device Connectors (FDC)

### Additional Product Information

Key Commercial Data

Orderkey 1413476

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 303 (PC-2011)

GTIN 4046356475815

Weight per Piece (excluding packing) 173.080 g

Custom tariff number 85444210

Country of origin DE (Germany)

Ambient conditions

Degree of protection IP67

General data

Number of positions 8

Degree of pollution 3  
Alternative short product description Ethernet cable  
Standards and Regulations  
Flammability rating according to UL 94 V2  
Cable  
Cable type Ethernet drag chain CAT5  
Cable type (abbreviation) 94C  
UL AWM style 20963 (80°C/30 V)  
Signal type/category Ethernet CAT5 (IEC 11801), 1 Gbps  
Cable structure 4x2xAWG26/19; S/UTP  
Conductor cross section 4x 2x 0.14 mm<sup>2</sup>  
AWG signal line 26  
Conductor structure signal line 19x 0.10 mm  
Core diameter including insulation 1 mm  
Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown  
Twisted pairs 2 cores to the pair  
Overall twist Four pairs and four fillers to the core  
Shielding Tinned copper braided shield  
Optical shield covering 90 %  
External sheath, color water blue RAL 5021  
Outer sheath thickness 0.85 mm  
External cable diameter D 6.9 mm +0.1 mm ... 0.2 mm  
Minimum bending radius, fixed installation 4 x D  
Minimum bending radius, flexible installation 8 x D  
Number of bending cycles 5000000  
Minimum bending radius, drag chain applications 7,5 x D  
Traversing rate 3 m/s  
Acceleration 5 m/s<sup>2</sup>  
Tensile strength GRP <= 100 N  
Cable weight 57 kg/km  
Outer sheath, material PUR  
Material co...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-M12FSBP-IP67/B-94C-LI/2,0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.