


INDUSTRIAL COMPONENT DATA

K-5E OE/010-C05/M40 F8 1620318 PHOENIX CONTACT Cable plug in molded plastic

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-5E - OE/010-C05/M40 F8



Manufacturer	PHOENIX CONTACT
MPN / Reference	K-5E - OE/010-C05/M40 F8
Catalog number	1620318
Category	Flexible cable
Minimum order	2 Pcs
Document ID	EO-10E215E891
Generated	2026-08-06

Product Overview

Cable plug in molded plastic

Plastic coated cable plug, series: KSM, M40-Female, straight coated by plastic extrusion, number of poles: 2+3+PE, Lock type: Screw lock, cable length: 10 m, shielded: yes, outer sheath color: orange RAL 2003

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1620318

Packing unit 1 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 230 (C-2-2017)

GTIN 4046356833523

Weight per Piece (excluding packing) 2,220.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Conductor length 10 m

Nominal current 44 A

Connector specifications

Type straight plastic-sheathed
Thread type M40
Locking type Screw locking
Degree of protection IP67, when in locked state
Number of positions 2+3+PE
Direction of rotation Standard
Type of contact Socket
Insertion/withdrawal cycles 50
Contact resistance < 0.3 mΩ
Max. current 70 A
Voltage 630 V
Overvoltage category III
Degree of pollution 3
Rated surge voltage 6 kV
Ambient temperature (operation) -40 °C ... 105 °C
Cable specifications
Type of cable PSLC11Y-J
Shielded yes
Cable structure 4 x 6 mm² + 2 x 1.5 mm²
Cable structure (AWG) 10 AWG/4c + 16 AWG/1pr
External cable diameter 16.3 mm
Outer sheath, material PUR
Material wire insulation TPE
External sheath, color orange RAL 2003
Nominal voltage, cable 1000 V
Test voltage 4 kV (1 kV signal)
Rated current 44 A
Smallest bending radius, fixed installation 66 mm
Smallest bending radius, movable installation 122 mm
Ambient temperature for fixed installation -50 °C ... 90 °C
Ambient temperature for flexible installation -40 °C ... 80 °C
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-5E - OE/010-C05/M40 F8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.