

INDUSTRIAL COMPONENT DATA

K-7E OE/2,0-D01/M17 F8 1619313 PHOENIX CONTACT Cable plug in molded plastic

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-7E-OE/2,0-D01/M17 F8



Manufacturer	PHOENIX CONTACT
MPN / Reference	K-7E-OE/2,0-D01/M17 F8
Catalog number	1619313
Category	Power cable less 1 kV, for moving application
Minimum order	2 Pcs
Document ID	EO-8169BBD246
Generated	2026-08-05

Product Overview

Cable plug in molded plastic

Plastic coated cable plug, series: KST, M17-Female, straight coated by plastic extrusion, number of poles: 7+PE, Lock type: Screw lock, cable length: 2 m, shielded: yes, outer sheath color: orange RAL 2003

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1619313

Packing unit 1 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 225 (C-2-2017)

GTIN 4046356828970

Weight per Piece (excluding packing) 473.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Conductor length 2 m

Nominal current 15 A

Connector specifications

Type straight plastic-sheathed
Housing material Zinc die-cast
Thread type M17
Locking type Screw locking
Degree of protection IP67, when in locked state
Number of positions 7+PE
Direction of rotation Standard
Type of contact Socket
Insertion/withdrawal cycles 50
Contact resistance < 0.3 mΩ
Max. current 14 A
Voltage 630 V
Overvoltage category III
Degree of pollution 3
Rated surge voltage 6 kV
Ambient temperature (operation) -40 °C ... 105 °C
Cable specifications
Type of cable PSLC11Y-J
Shielded yes
Cable structure 4 x 1 mm² + 2 x 2 x 0.75 mm² StC
Cable structure (AWG) 18 AWG/4c + 19 AWG/2pr
External cable diameter 11 mm
Outer sheath, material PUR
Material wire insulation TPM
External sheath, color orange RAL 2003
Nominal voltage, cable 1000 V
Test voltage 4 kV (2 kV signal)
Rated current 15 A
Smallest bending radius, movable installation 110 mm
Ambient temperature for fixed installation -40 °C ... 80 °C
Ambient temperature for flexible installation -20 °C ... 60 °C
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-7E-OE/2,0-D01/M17 F8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.