

INDUSTRIAL COMPONENT DATA

K-5E OE/5,0-C00/M17 F8 1619308 PHOENIX CONTACT Cable plug in molded plastic

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-5E-OE/5,0-C00/M17 F8



Manufacturer	PHOENIX CONTACT
MPN / Reference	K-5E-OE/5,0-C00/M17 F8
Catalog number	1619308
Category	Power cable less 1 kV, for moving application
Minimum order	2 Pcs
Document ID	EO-8DFC6D566A
Generated	2026-08-06

Product Overview

Cable plug in molded plastic

Plastic coated cable plug, series: KST, M17-Female, straight coated by plastic extrusion, number of poles: 5+PE, Lock type: Screw lock, cable length: 5 m, shielded: yes, outer sheath color: orange RAL 2003, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1243430

Cable connector overmolded, series: KST, M17 socket, straight plastic overmolded, number of poles: 5+PE, locking type: screw lock, cable length: 5 m, shielded: yes, color outer jacket: orange RAL 2003, alternative product according to RoHS II without exception 6c (Pb < 0.1 %) Item no.: 1243430

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1619308

Packing unit 1 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 224 (C-2-2017)

GTIN 4046356828925

Weight per Piece (excluding packing) 3.330 g

Custom tariff number 85444290

Country of origin DE (Germany)
Conductor length 5 m
Nominal current 12 A
Connector specifications
Type straight plastic-sheathed
Housing material Zinc die-cast
Thread type M17
Locking type Screw locking
Degree of protection IP67, when in locked state
Number of positions 5+PE
Direction of rotation Standard
Type of contact Socket
Insertion/withdrawal cycles 50
Contact resistance < 0.3 mΩ
Max. current 14 A
Voltage 630 V
Overvoltage category III
Degree of pollution 3
Rated surge voltage 6 kV
Ambient temperature (operation) -40 °C ... 105 °C
Cable specifications
Type of cable PSLC11Y-J
Shielded yes
Cable structure 4 x 0.75 mm² + 2 x 0.5 mm² StC
Cable structure (AWG) 19 AWG/4c + 20 AWG/1pr
External cable diameter 9.4 mm
Outer sheath, material PUR
Material wire insulation TPM
External sheath, color orange RAL 2003
Nominal voltage, cable 1000 V
Test voltage 4 kV (2 kV signal)
Rated current 12 A
Smallest bending radius, movable installation 94 mm
Ambient temperature for fixed installation -40 °C ... 80 °C
Ambient temperature for flexible installation -30 °C ... 70 °C
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Categ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-5E-OE/5,0-C00/M17 F8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.