


## INDUSTRIAL COMPONENT DATA

# K-7E OE/5,0-D02/M23 FK 1620422 PHOENIX CONTACT Cable plug in molded plastic

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-7E-OE/5,0-D02/M23 FK



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                               |
| MPN / Reference | K-7E-OE/5,0-D02/M23 FK                        |
| Catalog number  | 1620422                                       |
| Category        | Power cable less 1 kV, for moving application |
| Minimum order   | 2 Pcs                                         |
| Document ID     | EO-4722656B61                                 |
| Generated       | 2026-08-05                                    |

## Product Overview

Cable plug in molded plastic

Plastic-coated cable plug, length: 5 m, outer wrap colour: orange RAL 2003

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

Key Commercial Data

Orderkey 1620422

Packing unit 1 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 228 (C-2-2017)

GTIN 4046356831819

Weight per Piece (excluding packing) 1,279.800 g

Custom tariff number 85444290

Country of origin DE (Germany)

Conductor length 5 m

Nominal current 18 A

Connector specifications

Type Angled, can be turned, plastic-coated

Thread type M23  
Locking type Screw locking  
Degree of protection IP67, when in locked state  
Number of positions 4+3+PE  
Direction of rotation Standard  
Type of contact Socket  
Insertion/withdrawal cycles 100  
Contact resistance < 0.3 mΩ  
Max. current 30 A  
Voltage 630 V  
Overvoltage category III  
Degree of pollution 3  
Rated surge voltage 6 kV  
Ambient temperature (operation) -40 °C ... 105 °C  
Cable specifications  
Type of cable PSLC11Y-J  
Shielded yes  
Cable structure 4 x 1.5 mm<sup>2</sup> + 2 x 2 x 0.75 mm<sup>2</sup> StC  
Cable structure (AWG) 16 AWG/4c + 19 AWG/2pr  
External cable diameter 11.7 mm  
Outer sheath, material PUR  
Material wire insulation TPM  
External sheath, color orange RAL 2003  
Nominal voltage, cable 1000 V  
Test voltage 4 kV (2 kV signal)  
Rated current 18 A  
Smallest bending radius, movable installation 117 mm  
Ambient temperature for fixed installation -40 °C ... 80 °C  
Ambient temperature for flexible installation -20 °C ... 60 °C  
Environmental Product Compliance  
REACH SVHC Lead 7439-92-1  
China RoHS Environmentally Friendly Use Period = 50  
For details about hazardous substances go to tab "Downloads", Category "M..."

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-7E-OE/5,0-D02/M23 FK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.