

INDUSTRIAL COMPONENT DATA

SAC-3P-100,0-116/0,75 1457416 PHOENIX CONTACT Cable reel

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-100,0-116/0,75



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-100,0-116/0,75
Catalog number	1457416
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-6E663D2CEF
Generated	2026-08-04

Product Overview

Cable reel

By the metre, Cable ring, PUR/PVC, black RAL 9005, 3-conductors, colour single conductors: black 1, black 2, green/yellow, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1457416

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 169 (C-4-2013)

GTIN 4046356617543

Weight per Piece (excluding packing) 4,996.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 100 m

General

Number of positions 3

Cable

Cable type PUR/PVC, 0.75 mm², black

Cable type (abbreviation) 116

Cable abbreviation LiYY11Y

UL AWM style 20549

Conductor cross section 3x 0.75 mm²

AWG signal line 18

Conductor structure signal line 24x 0.20 mm

Core diameter including insulation 1.7 mm ±0.05 mm

Wire colors black 1, black 2, green/yellow

Overall twist 3 wires, twisted

External sheath, color black RAL 9005

External cable diameter D 5.8 mm ±0.2 mm

Minimum bending radius, flexible installation 10 x D

Number of bending cycles 1000000

Traversing rate 2 m/s

Acceleration 2.5 m/s²

Outer sheath, material PUR

Material, inner sheath PVC

Material conductor insulation PVC

Conductor material Bare Cu litz wires

Insulation resistance ≥ 20 MΩ·km

Conductor resistance 26 Ω/km (at 20 °C)

Nominal voltage, cable 300 V

Test voltage, cable 1200 V

Special properties flexible

Flame resistance DIN VDE 0482

DIN EN 50265-2-1

in acc. with UL FT-2

Other resistance Low adhesion

Ambient temperature (operation) -40 °C ... 80 °C (cable, fixed installation)

-5 °C ... 80 °C (cable, flexible installation)

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-100,0-116/0,75 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.